

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:


0 580 897 A1

(12)

EUROPEAN PATENT APPLICATION(21) Application number: **92121293.2**(51) Int. Cl.⁵: **B05B 11/02**(22) Date of filing: **15.12.92**(30) Priority: **03.06.92 IT MI921370**(43) Date of publication of application:
02.02.94 Bulletin 94/05(84) Designated Contracting States:
**AT BE CH DE DK ES FR GB GR IE IT LI LU MC
NL PT SE**(71) Applicant: **ELETTRO PLASTICA S.p.A.**
Via Lambro, 86
I-20089 Quinto de Stampi-Rozzano
(Milano)(IT)(72) Inventor: **Marelli, Andrea**
Via Lambro, 86
I-20089 Rozzano (MI)(IT)(74) Representative: **Giambrocono, Alfonso, Dr.**
Ing. et al
Ing. A. Giambrocono & C. S.r.l.
Via Rosolino Pilo 19/B
I-20129 Milano (IT)(54) **Single-dose nasal dispenser for atomized liquid drugs.**

(57) The invention relates to a manually actuated nasal dispenser, suitable for dispensing a liquid single dose in atomized form retained in a chamber (2) which is part of said dispenser: said liquid consisting of or containing a substance having pharmaceutical activity, for instance calcitonin.

Said nasal dispenser has a very simple structure, it assures a perfect seal and insulation of the liquid retained in it till the moment of its use, and it is made in such a way that the dispensing of the liquid in atomized form occurs only after that at least a minimum pressure having a predetermined value has been given, thus avoiding droppings of said liquid outside of the dispenser discharging nozzle (12).

*Fig. 1***EP 0 580 897 A1**

The invention relates to a manually actuatable dispenser for dispensing dosed amounts of liquid drugs in atomized form.

It is known that many drugs, for instance calcitonin, are nasally administered: since these drugs are extremely expensive and sometimes they can cause undesired side effects if they are sprayed into nose in exceeding doses, some devices are used for their application by which an exactly predetermined liquid amount, in a totally atomised form, can be dispensed, leaving the lowest residual possible of said liquid unused in said devices.

Indeed, it often happens that the known devices are not suitable for dispensing practically all the liquid substance therein retained, or that the dispensing occurs also at a relatively low pressure, with consequent dropping (and therefore loss) of said liquid outside of the dispensing nozzle of the nasal distributor, or further that the devices have a very complicated structure and therefore extremely expensive, to such an extent to suggest sometimes, at least in part, their re-use.

Devices of such a type are, for instance, described in the patents EP-B-0218840 corresponding to the US-A-4.921.142 patent, and in the improvement of said last patent, depicted in the EP-A-0388651 and in the PCT/WO/91/13689 (PCT/EP91/00457 application) patents, besides that in the EP-A-0452728 patent.

All the above mentioned patents describe nasal dispensers having a rather complicated structure and therefore expensive, some of which, at the end of their use, keeping in their inside a remarkable amount of the liquid, others not assuring a sufficient seal and insulation of said liquid in the inside of the device during the storage, further, others allowing the liquid dispensing even at excessively low dispensing pressures, with consequent liquid dropping.

To simplify the structure and to therefore control the expenditures of such devices, the French patent FR-B-2625981 proposed a nasal dispensing device comprising a seat in which a piston, which is part of the device itself, extends, in said seat a cylindrical ampoule being insertable which holds the desired amount of the liquid: when said ampoule is inserted in the mentioned seat, the piston, which is part of the device, penetrates in the inside of the ampoule itself, thus allowing the expulsion of the liquid in atomized form when said ampoule is pushed inside its own seat.

The main purpose of the present invention is that one to realise a nasal dispenser of the above cited type, comprising a container of a single dose of a liquid having pharmaceutical activity, manually actuatable for dispensing practically totally such a dose of the liquid, at a dispensing pressure always higher than a minimum predetermined value.

Another purpose of the invention is that one to realise a nasal dispenser of the above mentioned type which assures, before manually actuating said device, a perfect seal and insulation of the liquid therein contained, the dispenser having, besides, a very simple structure and being extremely cheap.

The above purposes are achieved by a manually actuated nasal dispenser for dispensing dosed amounts of atomized liquid drugs, comprising a first body having a cylindrical chamber for containing at least one liquid drug dose and a second body slidably mounted on said first body and having a nozzle for drug dispensing, said first body having an elongated shape and delimiting said chamber which is open at one end of said first body itself whose other end has a seat for the resting of a finger of one hand, and said second body consisting of a hollow elongated element of rounded shape from which at least one shaped element externally extends for the resting of at least another finger of said hand and into which a tubular wall extends to which a piston slidable within said chamber is integral, said nozzle being provided in said hollow element in correspondence of a free end thereof, characterized in that one end of an elongated cylindrical stem, is inserted and retained said stem extending beyond the free edge of said tubular wall and having its other end extending into said chamber, said piston comprising a tubular sleeve made of resiliently yielding material superimposed to said stem, one end portion of said sleeve being mounted and retained on said tubular wall while the other end portion of the same sleeve extends and is seal slidable in said chamber, the intermediate portion of said sleeve consisting of a continuous wall resiliently flexible from which at least one annular continuous rib projects towards the inside, said rib being resiliently pushed on said stem to seal on it in rest condition of the dispenser, at least one continuous passage being formed between the internal surface of said sleeve and respectively the external surface of said stem, such passage being open at its ends in correspondence of said nozzle and respectively of said chamber and being seal intercepted, in an intermediate position, by said rib protruding from said intermediate portion of said sleeve.

Conveniently, said first and second bodies have shaped portions and cooperating among them to prevent the free ends of said stem and of said sleeve from discharging from said chamber and retaining means are provided which can be snapped upon manual actuation of said dispenser for retaining said first and second bodies in the resting position preliminary to dispensing.

A preferred embodiment of the invention shown by mere and non limiting example will be now described to make the structure and the features of

the nasal dispenser according to the present invention clearer, reference being made to the accompanying drawing wherein:

- Figure 1 is an enlarged cross-section, of a single dose nasal dispenser according to the invention whereof
- Figures 2 and 3 respectively represent, in frontal elevation, the end portion in two different blocked positions of the two dispenser components which are movable one upon the other.

The dispenser illustrated in the drawings comprises a first body 1 which defines a cylindrical chamber 2 suitable for containing a dose of a liquid drug, and a second body 3 slidably mounted on said body 1 by manual action, such bodies being preferably made of plastics, by molding.

Said body 1 has an elongated shape and it delimits the above said chamber 2 which is open in correspondence of the upper end (with respect to Figure 1) of the body itself, whose lower end has a seat 4 for the thumb of one hand by which the dispenser is actuated.

Said body 3 consists of an elongated hollow element 3A having a rounded profile (as it can be clearly seen from Figure 1) from whose lower end (with respect to said Figure 1) it externally protrudes a wing 5 whereon two fingers of a hand can lean, and whose thumb is leant on the seat 4, at the moment of the dispenser actuation: in the inside of the hollow element 3A, it extends a tubular wall 6, wherein it is inserted and retained the upper end of a cylindrical elongated stem 7 which extends beyond and under the lower edge of said tubular wall and whose other end, namely the lower end of said stem, extends and is slidable into said chamber 2, as it can be clearly seen from Figure 1.

The stem 7 is surrounded by a tubular sleeve 8, 9, 10 made of rubber or of other suitable resiliently yielding material. The portion of the sleeve upper end 9 is mounted and steadily retained on the lower end of said tubular wall 6, while the portion of the lower end thereof is internal to said chamber 2 and it is seal slidable on the cylindrical surface of said chamber.

The intermediate portion 8 of the sleeve consists of a resiliently flexible continuous wall wherefrom it extends towards the inside a continuous annular rib 11 which is resiliently pushed on said stem 7, making seal on it: consequently the intermediate portion 8 of the sleeve takes a "barrel" shape, namely its longitudinal sections are arch shaped, as it can be clearly seen from Fig. 1.

It can be noticed from the drawing that, among the external surface of said stem 7 and the internal surfaces of the sleeve 8, 9, 10 respectively, a continuous passage is delimited (not indicated with reference numbers in the drawing, but provided all

around said stem) which is closed, at one of its intermediate positions, by said rib 11 which is kept pressed on said stem 7 by the resilient action of the portion 8 of the sleeve. Said passage opens in correspondence of the upper end 3A of said body 3, where the discharge nozzle 12 is provided wherefrom the liquid drug in atomized form can be discharged.

The above continuous passage can be made for instance, getting one or more grooves in the lower portion and in the upper one of said stem 7 or providing a series of projections in the inside of the portions 9 and 10 of the sleeve.

A protecting cap (not represented in the drawing) can be mounted and snap-retained on the body 3, said cap having to be obviously removed before using the nasal dispenser.

Reference be now made also to Figures 2 and 3. It can be therefrom seen that in the lower part 3B of the body 3 it is got one elongated and shaped window one of whose parts 20 extends longitudinally and has, near its lower portion, a relief 21 in correspondence of which there extends a substantially horizontal part 22 of the window delimited by two projections indicated by the numbers 23 and 25 respectively.

Radially towards the inside, from the body 1 it extends a stem 25 which is inserted and is slidable in the above mentioned window parts 22 and 20.

In the phase of preparing the dispenser, at first the body 1 is moved into the body 3, making the stem 25 slide in the window or slit at the lower end 3B of the body 3, till said stem snap-passes beyond the relief 24, disposing itself and being retained in a tight manner in the first horizontal part 22 of the window, being therein blocked between the projections 23 and 24 (Fig. 2).

Obviously before mounting the body 3 on the body 1, the desired amount of the liquid drug is inserted into the chamber 2, being said drug destined to be dispensed by the dispenser.

It has to be noticed that when in the phase of the dispenser mounting, the stem 7 and the lower portion 10 of the sleeve 8, 9, 10 are moved into the chamber 2: the air therein present upon the surface of the liquid already introduced in said chamber, passes into the free space between said stem and the portion 10 of the sleeve and causes a ball-like swelling of the portion 8 with the consequent lifting of the rib 11 away from said stem 7, in such a way that the air can be discharged towards the outside through the nozzle 12.

When the movement of introducing the stem and the sleeve is ceased, the pressure within the chamber lowers, reaching an equilibrium value, and the rib 11 resiliently and automatically makes back seal on the surface of the stem 7.

This being made, the dispenser is ready for the use.

It has to be noticed that in said conditions, unintentional dispensing of the liquid contained in the chamber 2 is not attained, said liquid remaining hermetically closed in the chamber itself, the stem 25 being retained in the position depicted in Figure 2.

Supposition be now made wanting to use the dispenser: catching with two hands the body 3 and the lower part of the dispenser respectively, a rotation is caused, of the one in respect to the other, around their axis, in such a way that the stem 25 snap-passes the projection 23, disposing itself in the position shown in Figure 3, wherein it is retained between said projection 23 and the projection 21.

The thumb of one hand is then lent on the free end 4 of the body 1 and the forefinger and the medium finger of the same hand are lent on the wings 5 exerting a high pressure which causes the snap-passing of the stem 25 beyond the holding edge 21, thus transmitting a pressure, having since from the start already a very high value to the liquid contained in the chamber 2.

Said liquid after having passed in the open space between the stem and the facing surface of the portion 10 of the sleeve, causes the buckling or swelling towards the outside of the intermediate portion 8 of such sleeve and then the lifting of the annular rib 11 away from the surface of the stem 7, thus allowing the ejection of the liquid drug which passes from the chamber 2 beyond the annular rib 11, crosses the space delimited among the external surface of the stem and the internal surfaces of the sleeve and of the tubular element 6 and discharges under pressure and in finely atomized form through the discharging nozzle 12, to be inhaled in the nostril of the nose of the utilizer.

It can be noticed that the push exerted on the lower surface of the portion 10 of the sleeve by the liquid under pressure, contributes to arch towards the outside the intermediate rounded portion 8 of the sleeve itself and helps therefore the lifting of the rib 11 away from the surface of the stem 7, thus favouring the expulsion of the liquid from the chamber 2.

The structure of the nasal dispenser is rather simple and the cost thereof is low as it can be easily understood by what it has been above described; the liquid in the chamber 2 remains completely isolated before the dispenser use and, during its utilization, the dispensing occurs at a very high pressure of a predetermined value, thus avoiding every form of dropping of the liquid outside of the discharging nozzle.

It is also evident that the structure of the dispenser can be carried out in different forms but

equivalent to that one depicted in the drawings. For instance the retaining means of the stem 25, instead of being made up by the relief 21 and by the projections 23 and 24, can consist each of a thin wall or membrane carried out by molding together with the body 3, each of such walls or membranes being suitable to hold the stem 25 and being broken (in such a way that said stem can snap-pass beyond it) when said stem is pushed onto said membrane with a force sufficient to break the membrane itself.

Claims

1. Manually actuated nasal dispenser for dispensing dosed amounts of atomized liquid drugs, comprising a first body having a cylindrical chamber for containing at least one liquid drug dose and a second body slidably mounted on said first body and having a nozzle for drug dispensing, said first body having an elongated shape and delimiting said chamber which is open at one end of said first body itself whose other end has a seat for the resting of a finger of one hand, and said second body consisting of a hollow elongated element of rounded shape from which at least one shaped element externally extends for the resting of at least another finger of said hand and into which a tubular wall extends to which a piston slidable within said chamber is integral, said nozzle being provided in said hollow element in correspondence of a free end thereof, characterized in that one end of an elongated cylindrical stem, is inserted and retained said stem extending beyond the free edge of said tubular wall and having its other end extending into said chamber, said piston comprising a tubular sleeve made of resiliently yielding material superimposed to said stem, one end portion of said sleeve being mounted and retained on said tubular wall while the other end portion of the same sleeve extends and is seal slidable in said chamber, the intermediate portion of said sleeve consisting of a continuous wall resiliently flexible from which at least one annular continuous rib projects towards the inside, said rib being resiliently pushed on said stem to seal on it in rest condition of the dispenser, at least one continuous passage being formed between the internal surface of said sleeve and respectively the external surface of said stem, such passage being open at its ends in correspondence of said nozzle and respectively of said chamber and being seal intercepted, in an intermediate position, by said rib protruding from said intermediate portion of said sleeve.

2. Nasal dispenser according to claim 1 characterized in that said first and said second bodies have shaped portions and cooperating among themselves to prevent the free ends of said stem from discharging from said chamber. 5
3. Nasal dispenser according to claims 1 and 2 characterized in that retaining means are provided which can be snap-passed upon manual actuation of said dispenser for retaining said first and second bodies in the resting position preliminary to dispensing. 10

15

20

25

30

35

40

45

50

55

5




Fig. 1




Fig. 2




Fig. 3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 92 12 1293

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.5)
E	WO-A-9 300 172 (VALOIS S.A.) * page 8, line 35 - page 9, line 24; figures 6,7,9 *	1	B05B11/02
X	EP-A-0 201 701 (ING. ERICH PFEIFFER GMBH & CO. KG) * page 11; figures 2,3 *	1	
X	EP-A-0 212 188 (ING. ERICH PFEIFFER GMBH & CO. KG) * page 10; figure 1 *	1	
A	EP-A-0 486 894 (PROMO PACK SA) * column 6, line 14 - line 47; figure *	1	
A	EP-A-0 311 863 (ING. ERICH PFEIFFER GMBH & CO. KG) * column 10, line 23 - line 55; figures *	1-3	
A	EP-A-0 021 123 (HOECHST AKTIENGESELLSCHAFT) * page 3, line 23 - line 32; figure *	2,3	
			TECHNICAL FIELDS SEARCHED (Int. Cl.5)
			B05B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 01 SEPTEMBER 1993	Examiner BREVIER F.J.
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			
T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application I : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 01.92 (P0401)